



9200 Mold Resistant

J.A.W.S.™ Polyurethane Adhesive / Sealant

Description:

J.A.W.S.™ 9200 is a resilient polyurethane adhesive recommended for subfloor and general construction applications. It is designed to provide permanent bonding, vibration dampening and excellent adhesion to most common building materials.

Typical Uses:

- ▶ Stairs / handrail stacking
- ▶ Bedding window and door mounting flanges
- ▶ Bonding subfloors to joists
- ▶ Wood panels
- ▶ Bonding sidewall and trim in manufactured housing
- ▶ Excellent for sealing base plates to concrete slabs before anchoring.

Advantages:

- ▶ One component, polyurethane-based adhesive
- ▶ Suitable for interior or exterior applications
- ▶ Certified to meet AFG-01 requirements based on third party testing
- ▶ VOC compliant
- ▶ Adheres to wet and frozen lumber
- ▶ Resistant to mold growth

Specification Compliance:

AFG-01
ASTM C 557
ASTM D 3498



Typical Properties:

Property	Value	Test Method
Density	13.8 #/gal	ASTM D 1475
Extrudability	80 Sec.	ASTM D2452 20g through a 0.104" orifice @50psi
Tensile Strength	400 psi (2.75 N/mm ²)	ASTM D 412
Elongation	360%	ASTM D 412
VOC	125 g/l	
Flash Point	104°F (40°C)	Tag Closed Cup ASTM D 56
Lap Shear (pine)	390 psi (2.70 N/mm ²)	ASTM D 905
Cure Rate		1/4" bead at 75°F (23.8°C) and 50% R.H.
Firm Set	2-3 Hours	
Handleable	8-10 Hours	
Full Cure	48 Hours	
Shelf Life	J.A.W.S.™ 9200 has a 1 year shelf life when stored at or below 75°F and 50% R.H.	

Surface Preparation:

Surfaces must be structurally sound, clean, and free of dirt, loose particles, oil, grease, asphalt, tar, paint, wax, rust, waterproofing or other substances that may affect adhesion. On wood surfaces, the surface must be clean and sound. Scrape away paint and sand to bare wood. On concrete, stone, or other masonry surfaces, clean by grinding, sandblasting or wire brushing to expose a sound surface free of contamination and laitance. On metal surfaces, remove scale, rust or other coatings to expose a bright white surface.

Note: J.A.W.S.™ 9200 bonds well to most substrates; however, it is the user's responsibility to check the adhesion of the cured adhesive to their specific substrates.

Application:

- ▶ Trim nozzle to desired size opening.
- ▶ Place cartridge in caulking gun and puncture seal in the nozzle.
- ▶ Apply J.A.W.S.™ 9200 when temperature is above 40°F.
- ▶ When working on rough surfaces, use enough adhesive to fill gaps. 9200 will bridge gaps up to 3/8" wide.
- ▶ Use mechanical fasteners to hold the surfaces in place until the adhesive fully cures.

Clean-Up:

Clean all tools and excess J.A.W.S.™ 9200 immediately after use with Xylene or toluene. Cured adhesive can only be removed mechanically. The use of these solvents (or other solvents) may be hazardous to your health. Use only in ventilated areas. KEEP FROM OPEN FLAME. Read all labeling before use, and follow solvent manufactures recommendations and instructions for safe handling

It is recommended that gloves be worn during application. J.A.W.S.™ 9200 is difficult to remove from the skin and clothing. If adhesive gets on skin, immediately wipe off with a dry cloth.

PRO INSTALLER® WINDOW AND DOOR INSTALLATION SYSTEM LIMITED WARRANTY:

PRO INSTALLER® WARRANTS TO THE ORIGINAL RETAIL PURCHASER THAT THE PRO INSTALLER® WINDOW AND DOOR INSTALLATION WILL BE FREE FROM LEAKS CAUSED BY DEFECTS IN THE MATERIAL'S OR MANUFACTURING FOR A PERIOD OF FIFTEEN YEARS (15) FROM THE DATE OF PURCHASE WHEN THE SYSTEM IS INSTALLED ACCORDING TO THE MANUFACTURERS WRITTEN INSTRUCTIONS AND ACCEPTED INDUSTRY STANDARDS. THIS WARRANTY DOES NOT APPLY TO MISAPPLICATION OR POOR WORKMANSHIP IN THE APPLICATION OF THE SYSTEM AND SPECIFICALLY EXCLUDES: (A) NATURAL CAUSES SUCH AS ACTS OF GOD, EARTHQUAKE, LIGHTNING, HURRICANE, FIRE ETC, (B) DISINTEGRATION OF THE UNDERLYING SUBSTRATES, (C) MECHANICAL DAMAGE TO THE SYSTEM CAUSED BY INDIVIDUALS, TOOLS OR OTHER OUTSIDE AGENTS. PRO INSTALLER®S ONLY OBLIGATION SHALL BE TO RE-SUPPLY OR REFUND, AT ITS OPTION, THE PURCHASE PRICE OF THE PORTION OF THE DEFECTIVE SYSTEM WHERE THE LEAKS OCCURRED. PRO INSTALLER® SHALL BE LIABLE FOR NO ADDITIONAL REMEDIES, HEREBY EXPRESSLY DENYING ANY OTHER CLAIMS FOR DAMAGES, WHETHER DIRECT OR INDIRECT, CONSEQUENTIAL OR INCIDENTAL, INCLUDING BUT NOT LIMITED TO PROPERTY DAMAGE, PERSONAL INJURY TO THE BUYER OR TO THIRD PARTIES AND LOSS OF BUSINESS OR PROFIT ARISING FROM THE USE OR INABILITY TO USE THE SYSTEM. ANY IMPLIED WARRANTIES ARISING UNDER STATE LAW ARE LIMITED TO THE DURATION AND TERMS OF THIS EXPRESS WARRANTY.

THIS WARRANTY WILL BE NULL AND VOID IF SYSTEM COMPONENTS MADE BY MANUFACTURERS OTHER THAN PRO INSTALLER® ARE USED AS PART OF THE WINDOW AND DOOR INSTALLATION.

CURRENT SYSTEM COMPONENTS:

PRO INSTALLER® 7100 POLYURETHANE INSTALLATION SEALANT
PRO INSTALLER® 3300 FLASHING PRODUCT LINE, SAF™, PROSAF™, PROSAF™flex, PRO Flash™
PRO INSTALLER® 4300 POLYURETHANE AIR AND ENERGY POLYURETHANE FOAM
PRO INSTALLER® Mold Blocker™ Housewrap

ANY FUTURE SYSTEM COMPONENTS WILL ALSO BE COVERED BY THE ABOVE LIMITED WARRANTY.

Pro Installer®

Manufactured By:
Schnee-Morehead®, Inc.
111 North Nursery Road
Irving, Texas 75060
Phone: 972-438-9111 Fax: 972-554-3939
www.pro-installer.com